Declaration of performance

Number: 2023-006 Rijswaard facing brick

| (4) Manufacturer: | | | | | |
|---|--|---------------------------------------|----------------------|---|--|
| Steenfabriek De Rijswaard B.V. De Rijswaard 2 | | 0)418 - 55 22 21 (0)418 - 55 29 00 | RIJSWAARI BAKSTEE | D [®] | |
| VL-5308 LV AALST | www.rijsw | | BAKSTEEN | | |
| | | | | | |
| (1) Unique identification code of the product- type | Brons/G | Brons/Grijs | | | |
| 2) Typenumber | 10101313 Smoke G | 10101313 Smoke Grey Flame WF | | | |
| (3) Intended use or uses of the construction productbouwproduct | Units for use in unprotected masonry walls, colums and partitions. | | | | |
| (6) System or systems of assessment and verification of constancy of performance of the construction product | 2+ | | | | |
| 7) Notified body | Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the fa production control. | | | | |
| (9) Declared performance: | | | | | |
| Dimensions | | WF 210x100x50 | | | |
| ength | | 210 | m | U Metselbakstee Categorie I volgens EN77 1:2011 + A1:2015 | |
| Vidth | | 98 | mm | | |
| Height | | 49 | m | | |
| Dimensional tolerance | | T2 | | | |
| Range category | | R1 | | | |
| Flatness of bed faces | | NPD | | | |
| Parallellisme legvlakken | | NPD | | | |
| Gross dry density | | 1500 | kg/m3 | | |
| Net dry density | | NPD | kg/m3 | | |
| Tolerance Volumetric Mass: Class / % | | DM ±15 | % | | |
| Total volume frog | | <20% | | | |
| Group Eurocode | | 1 | | | |
| Mean compressive strength | | ≥ 15 | N/mm2 | | |
| Normalised compressive strength | | ≥ 15 | N/mm2 |] | |
| Bond strength | | 0.15 / 0.30 | | | |
| Thermal conductivity | | 50/50: 0.45 / 90/90: 0.48 | W/mK | EN 1745:2012 | |
| Nater vapour permeability | | 5/10 | | | |
| [Durability : freeze/thaw resistance] | | F2 | | | |
| Water absorption | | ≤ 18 % | m/md | | |
| Initial rate of water absorption | | <6 | kg/(m²min) | | |
| Active soluble salt content | | \$2 | | | |
| [Dimensional stability: Moisture movement] | | NPD | mm/m | | |
| Dangerous substances | | Voldoet | | NL-BBK | |
| Reaction to fire | | A1 | | | |

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by

Atse Blei General Management



Aalst (NL) 15-Jan-2025