Declaration of performance

Number: 2023-002 Rijswaard facing brick

Rijswaard facing brick					
(4) Manufacturer:					
Steenfabriek De Rijswaard B.V. De Rijswaard 2 NL-5308 LV AALST	Tel: +31 (0)418 - 55 22 21 Fax: +31 (0)418 - 55 29 00 www.rijswaard.nl		RIJSWAARD° BAKSTEEN		
(1) Unique identification code of the product- type	Geel/Naturel				
(2) Typenumber		104411713 Fawn Yellow Flame WF HV			
(3) Intended use or uses of the construction productbouwproduct	Units for u	Units for use in unprotected masonry walls, colums and partitions.			
(6) System or systems of assessment and verification of constancy of performance of the construction product	2+				
(7) Notified body	Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production con performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity production control.				
(9) Declared performance:					
Dimensions		WF 210x100x50			
Length			m	U Metselbaksteen Categorie I volgens EN771- 1:2011 + A1:2015	
dth		98	m		
Height		49	mm		
Dimensional tolerance		T2			
Range category		R1			
Flatness of bed faces		NPD			
Parallellisme legvlakken		NPD			
Gross dry density		1450	kg/m3		
Net dry density		NPD	kg/m3		
Tolerance Volumetric Mass: Class / %		DM ±15	%		
Total volume frog		<20%			
Group Eurocode		1			
Mean compressive strength		≥ 15	N/mm2		
Normalised compressive strength		≥ 15	N/mm2		
Bond strength		0.15 / 0.30			
Thermal conductivity		50/50: 0.41 / 90/90: 0.45	W/mK	EN 1745:2012	
Water vapour permeability		5/10			
[Durability : freeze/thaw resistance]		F2			
Water absorption		≤ 24 %	m/md	_	
Initial rate of water absorption		<8	kg/(m²min)		
Active soluble salt content		S2			
[Dimensional stability: Moisture movement]		NPD	mm/m		
Dangerous substances		Voldoet		NL-BBK	
Reaction to fire		A1			

53°C €

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by

Atse Blei General Management



Aalst (NL) 15-Jan-2025