Declaration of performance

Number: Rijswaard facing brick



(4) Manufacturer:		
Steenfabriek De Rijswaard B.V. De Rijswaard 2 NL-5308 LV AALST	Tel: +31 (0)418 - 55 22 21 Fax: +31 (0)418 - 55 29 00 www.rijswaard.nl	RIJSWAARD° BAKSTEEN
(1) Unique identification code of the product- type	Mangaan	
(2) Typenumber	105611013 Maasbruin HV WF	
(3) Intended use or uses of the construction productbouwproduct	Units for use in unprotected masonry walls, colums and partitions.	
(6) System or systems of assessment and verification of constancy of performance of the construction product	2+	
(7) Notified body	Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	
		·

(9) Declared performance:			
Dimensions	WF 210x100x50		
Length	209	mm	
Width	97	m	Metselbaksteen, Categorie I volgens EN771- 1:2011 + A1:2015
Height	49	mm	
Dimensional tolerance	T2		
Range category	R1		
Flatness of bed faces	NPD		
Parallellisme legvlakken	NPD		
Gross dry density	1600	kg/m3	
Net dry density	NPD	kg/m3	
Tolerance Volumetric Mass: Class / %	DM ±15	%	
Total volume frog	<20%		1
Group Eurocode	1		
Mean compressive strength	≥ 15	N/mm2	7
Normalised compressive strength	≥ 15	N/mm2	
Bond strength	0.15 / 0.30		7
Thermal conductivity	50/50: 0.49 / 90/90: 0.52	W/mK	EN 1745:2012
Water vapour permeability	5/10		
[Durability : freeze/thaw resistance]	F2		
Water absorption	≤ 15 %	m/md	
Initial rate of water absorption	<6	kg/(m²min)	
Active soluble salt content	S2		
[Dimensional stability: Moisture movement]	NPD	mm/m	7
Dangerous substances	Voldoet		NL-BBK
Reaction to fire	A1		

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of perfomance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behild of the manufacturer by

Atse Blei General Management

Aalst (NL) 15-Jan-2025